



Technical Data Sheet

A61-012
2 Mil Acrylic Transfer Adhesive

Description

2 Mil thick film of high performance solvent-free acrylic pressure sensitive adhesive.
Supplied on a gold 55# Glassine Liner
Used with wood, metal, foams, plastic, paper, cardboard, felt and fleece, or sheet materials.
Low VOC ratings – test data available upon request

Physical Properties

Physical Property	Test Method	Unit	Value
Adhesive Thickness		Mils	2
Coating Weight		G/M ²	45-55
Peel Adhesion: 180°	ASTM 3330	OZ/IN	65
Shear Adhesion: 23°C	ASTM 3654		1000g/625mm ²
Operating Temperature		°F	-22 to 248
Humidity/Moisture Resistance			Very Good
Plasticizer Resistance			Good
Aging Resistance			Very Good

Storage and Shelf Life: Recommend consuming all materials within a year of purchase. Material should be stored at 70°F, 50% relative humidity, out of direct sunlight.

Application: Surfaces should be clean and dry before application. Avoid touching adhesive surface.

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.