



Technical Data Sheet

A62-002

High Tack Acrylic Adhesive

Specifications

Material: High Tack Double Coated Acrylic Adhesive

Description: For use in a broad range of applications at both high and low temperatures. Features a modified acrylic ultra-high tack adhesive on a polyester carrier; supplied on a 74# polycoated kraft liner. Resistant to oils, chemicals, oxidation, humidity and UV. Adheres well to most low surface energy polyolefins, papers, vinyls, foams and metals. Excellent for extruded plastics.

Physical Properties

Technical Specifications

Physical Property	Test Method	Unit	Value
Product Thickness	PSTC-133	Mils	3.5
Adhesive Thickness – EXP			1.5
Adhesive Thickness – LNR			1.5
Peel Adhesion – EXP	PSTC-101	Oz/In	60
Peel Adhesion - LNR	PSTC-101	OZ/In	60
Shear Adhesion	PSTC-107		>24 Hrs. @ 2.2 psi
Tensile Strength	PSTC-131	Lb/In	7.5
Elongation		%	100
Service Temperature		° F	-40 to 225

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.