



Technical Data Sheet

A63-002
2 Mil Rubber Transfer Adhesive

Description

- A High Tack, Quick Stick adhesive
- Bonds to a wide range of materials, including foam, rubber cork, nonwovens, metals, plastics, and more.
- Provided on a 76# Poly-Coated release liner

Physical Properties

Physical Property	Test Method	Value	Unit
Thickness: Adhesive	PSTC-133 / ASTM D3652	2	MILS
Peel Adhesion: SS Air Side	ASTM D3330 / PSTC-101	118	OZ/IN
Peel Adhesion: ABS Air Side	ASTM D3330 / PSTC-101	107	OZ/IN
Polyken Probe Tack	ASTM D2979	>1675	G
Shear: Air Side	PSTC 107 / ASTM D3654	>10,000	Minutes
Elevated Temperature Test	Modified ASTM D4498	160	°F
Application Temperature		50-100	°F

Surface Preparation: Surface to which the tape is applied must be clean, dry and free of grease and oil.

Storage and Shelf Life: One year when stored at 70° and 50% relative humidity, out of direct light.

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.