



# Material Specification Sheet

## NV Series - Medium

Material: IV-2 Grade Closed Cell Vinyl Nitrile Sponge

Description: IV-2 Grade Closed Cell Vinyl Nitrile Sponge is used in a variety of tapes and gaskets requiring good chemical and fire resistance. This material is characterized by its uniform cell structure and good dimensional stability.

Technical Specifications				
Physical Property	U/M	Test Method	Value	Notes
		ASTM D 1056-68	SCE 42	
		ASTM D 1056-85, 91, 98	2B2	
Color		*	Black	
Compression Force Deflection	PSI	ASTM D 1056	7	+/-2 @ 25%
Compression Set	%	ASTM D 1056	35	Maximum based on compressed height
Density	PCF	ASTM 3575	6.5	+/-1
Elongation	%	ASTM D 412	100	Minimum
Flammability		UL-94 HF-1	Listed	@ minimum thickness of .058"
Flammability		UL-94 V-0	Listed	@ a minimum thickness of .456"
Flammability		FMVSS-302	Pass	
Maximum Temperature	F		200	
Minimum Temperature	F		-40	
Tensile Strength	PSI	ASTM D 412	75	
Water Absorption	%	ASTM D 1056	5	Max. weight change

\* Color

www.LAMATEK.com | 1-800-LAMATEK | 1226 Forest Parkway | West Deptford, NJ 08066