

Specifications

LB Series Polyurethane Bumpers are used in many applications: Drawer and Door Close, Electronics, Surface Protection, Anti-Skid, and many more.

Provided Kiss Cut in pads.

Standard colors are Clear and Black, with White, Grey and Brown available on request.

Please call for availability of profiles offered in SD.

Physical Properties

Physical Property	Standard Durometer	Soft Durometer
Tensile Strength (psi)	627 psi	750 psi
Elongation %	192	607
Tear Strength (pli)	214	127
Hardness, Shore A	60-70	50-55
Bashore Rebound %	27	35
Abrasion Resistance (g/1000 cycles Tabor H18, 1kg)	.016	.010
QUV (500 hrs)	Slight Yellowing	No Data Available
UL-94 HBF TESTING		PASSES:
Self-Extinguishing Time, Seconds	66.6 not heat aged – 72 heat aged	
Self-Extinguishing Length, Inches	.62 not heat aged - .52 heat aged	
Burn Rate, Inches per Minute	.02 not heat aged – no data available	

PLEASE NOTE THAT ALL DATA SHEETS ARE SUPPLIED BY LAMATEK, INC. WITH THE UNDERSTANDING THAT THE PURCHASER MUST DETERMINE THE SUITABILITY OF A PARTICULAR PRODUCT FOR ITS INTENDED PURPOSE. UNLESS OTHERWISE STATED, LAMATEK, INC. CANNOT WARRANT PRODUCTS IN THEIR APPLICATION.